Rittal - The System.

Faster – better – everywhere.

Plastic enclosures KSKS 1448.500

Date: Feb 1, 2017



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Plastic enclosures KS - KS 1448.500

created: 01.02.2017 on www.rittal.com/com-en



| D | 4 _ 1 _ | ! | 4! |
|-------|---------|-------|------|
| Produ | ict ae | SCrib | tion |

Material: Enclosure and door: Fibreglass-reinforced unsaturated polyester

Door: All-round foamed-in PU seal Mounting plate: Sheet steel

Viewing window: Glazed acrylic, 3.0 mm with all-round rubber cable clamp strip

Surface finish: Enclosure and door: Dyed plastic with no after-treatment

Mounting plate: Zinc-plated

Colour: Similar to RAL 7035

Protection category IP to IEC 60 529:

IP 56

Protection category NEMA:

NEMA 12

IK Code:

IK08

Supply includes:

Enclosure with hinged door, of all-round solid construction, 3 mm double-bit lock

Mounting plate

Twin seal on the top and bottom edges of the door as integral rain protection strip

Press-fitted C sections at the sides for infinitely variable mounting plate depth adjustment

Viewing window in the door

Note:

Under the influence of long-term UV radiation (sunlight) in conjunction with wind and rain, the surface finish may become visually impaired. This does not affect the protection of the installed electrical components in any way. If the enclosures cannot be protected from UV radiation, we recommend that they should be painted with a PUR paint. Ambient temperature -30°C...+75°C.

Product features

Dimensions: Width: 400 mm

© Rittal 2017

Height: 400 mm Depth: 200 mm

Viewing window: yes

Material thickness: Mounting plate: 2.5 mm

Mounting plate: Width: 345 mm

Height: 350 mm

Number of doors: 1

Door hinged on the right, may be swapped to the left:

yes

Lock version: Cam

Number of locks: 2

Lock insert: 3 mm double-bit

Packs of: 1 pc(s).

Weight/pack: 8 kg

EAN: 4028177526716

Customs tariff number:

94037000

ETIM 6.0: EC000261

ETIM 5.0: EC000261

e Cl@ss 8.0/8.1: 27180101

eCl@ss 7.0/7.1: 27180101

eCl@ss 6.0/6.1: 27180101

eCl@ss 5.1/5.1.4: 27180102

Approvals

Approvals: Bureau Veritas

Germanischer Lloyd

Lloyds Register of Shipping

Russian Maritime Register of Shipping

TÜV

© Rittal 2017

2

Certificates:

EAC IK-Code

Declarations:

Declaration of conformity

2017 © Rittal GmbH & Co. KG

© Rittal 2017

3