

# Rittal – The System.

Faster – better – everywhere.

## Plastic enclosures KS – KS 1449.500

Date : Dec 10, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Plastic enclosures KS – KS 1449.500

created : 10.12.2014 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Material:</b>	Enclosure and door: Fibreglass-reinforced unsaturated polyester Door: All-round foamed-in PU seal Mounting plate: Sheet steel Viewing window: Glazed acrylic, 3.0 mm with all-round rubber cable clamp strip
<b>Surface finish:</b>	Enclosure and door: Dyed plastic with no after-treatment Mounting plate: Zinc-plated
<b>Colour:</b>	Similar to RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 56
<b>Protection category NEMA:</b>	NEMA 12
<b>IK Code:</b>	IK08
<b>Supply includes:</b>	Enclosure with hinged door, of all-round solid construction, 3 mm double-bit lock Mounting plate Twin seal on the top and bottom edges of the door as integral rain protection strip Press-fitted C sections at the sides for infinitely variable mounting plate depth adjustment Viewing window in the door
<b>Note:</b>	Under the influence of long-term UV radiation (sunlight) in conjunction with wind and rain, the surface finish may become visually impaired. This does not affect the protection of the installed electrical components in any way. If the enclosures cannot be protected from UV radiation, we recommend that they should be painted with a PUR paint. Ambient temperature -30°C...+75°C.
<b>Packs of:</b>	1 pc(s).
<b>EAN:</b>	4028177526723

<b>Customs tariff number:</b>	94037000
<b>eCl@ss 5.1:</b>	27180102
<b>eCl@ss 7.0:</b>	27180101

## Product features

<b>Dimensions:</b>	Width: 400 mm Height: 600 mm Depth: 200 mm
<b>Viewing window:</b>	yes
<b>Mounting plate:</b>	Width: 345 mm Height: 550 mm
<b>Number of doors:</b>	1
<b>Number of cam locks:</b>	2
<b>Weight:</b>	11.2 kg

## Approvals

<b>Approvals:</b>	<a href="#">Bureau Veritas (EN)</a> <a href="#">Germanischer Lloyd (EN)</a> <a href="#">Lloyds Register of Shipping (EN)</a> <a href="#">Russian Maritime Register of Shipping (EN)</a> <a href="#">TUV EN</a>
<b>Certificates:</b>	<a href="#">IK-Code (EN)</a>
<b>Declarations:</b>	<a href="#">Declaration of conformity (DE)</a>

## Downloads

<b>Data sheets:</b>	<a href="#">Technical details (EN)</a>
<b>Documentation:</b>	<a href="#">Instructions (EN, DE)</a>
<b>CAD drawings:</b>	Request

Please note that there are the following alternative products:



Ex enclosures Plastic, empty enclosure with hinged door



# Rittal – The System.

---

**Faster – better – everywhere.**

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG  
Postfach 1662 · D-35726 Herborn  
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319  
E-Mail: [info@rittal.com](mailto:info@rittal.com) · [www.rittal.com](http://www.rittal.com)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP