

Rittal – The System.

Faster – better – everywhere.

Plastic enclosures AX with viewing window – AX 1479.000

Date : Dec 16, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Plastic enclosures AX with viewing window – AX 1479.000

created: 16.12.2020 build on www.rittal.com/uk-en



Product description

Design: with viewing window

Applications: Ambient temperature range: -35 °C...+80 °C
The specified temperatures may be limited by the installed equipment

Material: Enclosure and door: Fibreglass-reinforced unsaturated polyester
Door: All-round foamed-in PU seal
Mounting plate: Sheet steel
Viewing window: Polycarbonate
Fire protection corresponding to UL 94-V0

Surface finish: Enclosure and door: Dyed plastic with no after-treatment
Mounting plate: Zinc-plated

Colour: Similar to RAL 7035

**Protection category
IP to IEC 60 529:** IP 56

**Protection category
NEMA:** NEMA 12

**Type rating to UL
508A:** Type 12

IK Code: IK08

Protection class: II (at 1000 V AC)

Supply includes: Enclosure with hinged door with viewing window, of all-round solid construction, 3 mm double-bit lock

Door hinged on the right, may be swapped to the left
Mounting plate
Twin seal on the top and bottom edges of the door as integral rain protection strip

Note:	Interior installation screws are required to secure components inside the enclosure Components such as punched sections with mounting flanges may be attached on a 25 mm pitch pattern using the universal bracket
Basic material:	Plastic
Product features	
Dimensions:	Width: 800 mm Height: 1000 mm Depth: 300 mm
Viewing window:	yes
Material thickness:	Mounting plate: 2.5 mm
Mounting plate:	Width: 705 mm Height: 925 mm
Number of cam locks:	3
Packs of:	1 pc(s).
Weight/pack:	33.2 kg
EAN:	4028177007048
Customs tariff number:	94037000
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	AX compact enclosure, plastic, WHD: 800x1000x300 mm, with viewing window