## **Rittal – The System.**

Faster – better – everywhere.

## Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2246.605

Date : Jun 18, 2018



ENCLOSURES

ER DISTRIBUTION SCLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

## Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2246.605

created: 18.06.2018 on www.rittal.com/com-en



## **Product description**

Design:	with mounting plate and mounting angles, static installation
Description:	Wall-mounted enclosure with optimum accessibility due to hinged part.
Material:	Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Colour:	Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey)
Protection category IP to IEC 60 529:	IP 55
Supply includes:	Wall section with solid gland plate, top and bottom and mounting plate (supplied loose) Hinged part with 25 mm pitch pattern of holes in the front and rear frame, and two 482.6 mm (19") mounting angles, front, static installation Designer glazed door 1 double-kit key no. 5 Mini-comfort handle Security lock 3524 E
Basic material:	Sheet steel
Product features	
Dimensions:	Width: 600 mm

Height: 345 mm Units: 6 U Depth: 373 mm

Depth hinged part:	216 mm
Installation depth:	320 mm
Clearances:	Clearance width: 502 mm Clearance height: 282 mm
Mounting plate:	Width: 485 mm Height: 299 mm
Wall section:	Depth: 135 mm
Load capacity:	Hinged part, static (max.): 300 N
Packs of:	1 pc(s).
Weight/pack:	24.97 kg
EAN:	4028177324312
Customs tariff number:	94032080
ETIM 6.0:	EC002500
ETIM 5.0:	EC002500
eCl@ss 8.0/8.1:	27180208
eCl@ss 7.0/7.1:	27180208
eCl@ss 6.0/6.1:	27180208
eCl@ss 5.1/5.1.4:	27180204
Product description (long):	EL Wall-mounted enclosures, 3-part, 6 U, WHD: 600x345x373 mm, Protection category: IP 55, Designer glazed door
Approvals	
Approvals:	Germanischer Lloyd Lloyds Register of Shipping UL + C-UL
Certificates:	EAC Protection category