

Rittal – The System.

Faster – better – everywhere.

► Connection components for signal pillars, modular – SG 2368.000

Date : Feb 5, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Connection components for signal pillars, modular – SG 2368.000

created: 05.02.2018 on www.rittal.com/com-en



Product description

Design: for conduit mounting

Description: Optionally for conduit or wall/base mounting. Screw terminals in the connection component. With cover for optical components. Contact hazard protection to VDE.

Benefits: Simple assembly and contact via bayonet fastener.

Function principle: A modular layout is possible with connection, optical and acoustic components, incandescent lamps and a label panel.

Material: Enclosure of polyamide

Colour: Black

**Protection category
IP to IEC 60 529:** IP 54

Product features

Dimensions: Height: 43 mm
Diameter: 70 mm

**Rated operating
voltage:** 12 V - 240 V (AC/DC)

To fit signal pillar: modular

Diameter: 70 mm

Rated insulation voltage:	250 V AC
Rated impulse withstand voltage, phase to phase:	2500 V AC
Packs of:	1 pc(s).
Weight/pack:	0.12 kg
EAN:	4028177219908
Customs tariff number:	39269097
ETIM 6.0:	EC001152
ETIM 5.0:	EC001152
eCl@ss 8.0/8.1:	27371232
eCl@ss 7.0/7.1:	27371232
eCl@ss 6.0/6.1:	27371232
eCl@ss 5.1/5.1.4:	27371220
Product description (long):	SG Connection element, for signal pillar, modular, for conduit mounting
Approvals	
Approvals:	C-UL UL + C-UL UR
Certificates:	EAC
Declarations:	Declaration of conformity