

Faster – better – everywhere.





SG 2368.002 Connection component

CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 08/02/2023 (Source: rittal.com/com-en)

POWER DISTRIBUTION



FRIEDHELM LOH GROUP

ENCLOSURES

SG 2368.002 - Connection component for signal pillar, modular

Optionally for conduit or wall/base mounting. Screwless spring terminals in the connection component. With cover for optical components. Contact hazard protection to VDE.

Features

Model No.	SG 2368.002
Design	for wall/base mounting
Product description	Optionally for conduit or wall/base mounting. Screwless spring terminals in the connection component. With cover for optical components. Contact hazard protection to VDE.
Benefits	Simple assembly and contact via bayonet fastener.
Function principle	A modular layout is possible with connection, optical and acoustic components and a label panel
Material	Enclosure of polyamide
Colour	Black
Signal pillar	modular
Protection category to IEC 60 529	IP 65
Rated operating voltage	12 V - 230 V (AC/DC)
Packs of	1 pc(s).
Weight/pack	0.099 kg
Copper weight (kg per piece)	0
Customs tariff number	39269097
EAN	4028177953581
ETIM 7.0	EC001152
ECLASS 8.0	27371232

Approvals

Approvals

GOST UL + C-UL (listed)

Explanations

Declaration of conformity