

# Rittal – The System.

Faster – better – everywhere.

## ► Connection components for signal pillars, modular – SG 2368.010

Date : Feb 5, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Connection components for signal pillars, modular – SG 2368.010

created: 05.02.2018 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

**Design:** for wall/base mounting

**Description:** Optionally for conduit or wall/base mounting. Screw terminals in the connection component. With cover for optical components. Contact hazard protection to VDE.

**Benefits:** Simple assembly and contact via bayonet fastener.

**Function principle:** A modular layout is possible with connection, optical and acoustic components, incandescent lamps and a label panel.

**Material:** Enclosure of polyamide

**Colour:** Black

**Protection category  
IP to IEC 60 529:** IP 54

## Product features

**Dimensions:** Height: 43 mm  
Diameter: 70 mm

**Rated operating  
voltage:** 12 V - 240 V (AC/DC)

**To fit signal pillar:** modular

**Diameter:** 70 mm

<b>Rated insulation voltage:</b>	250 V AC
<b>Rated impulse withstand voltage, phase to phase:</b>	2500 V AC
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	0.12 kg
<b>EAN:</b>	4028177219915
<b>Customs tariff number:</b>	39269097
<b>ETIM 6.0:</b>	EC001152
<b>ETIM 5.0:</b>	EC001152
<b>eCl@ss 8.0/8.1:</b>	27371232
<b>eCl@ss 7.0/7.1:</b>	27371232
<b>eCl@ss 6.0/6.1:</b>	27371232
<b>eCl@ss 5.1/5.1.4:</b>	27371220
<b>Product description (long):</b>	SG Connection element, for signal pillar, modular, for wall/base mounting
<b>Approvals</b>	
<b>Approvals:</b>	C-UL UL + C-UL UR
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity