

Rittal – The System.

Faster – better – everywhere.

► Acoustic components for signal pillars, modular – SG 2376.000

Date : Feb 5, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Acoustic components for signal pillars, modular – SG 2376.000

created: 05.02.2018 on www.rittal.com/com-en



Product description

Design:	Continuous tone or pulsating, 85 dB, max. 25 mA
Description:	To indicate warnings or malfunctions.
Benefits:	Simple assembly and contact via bayonet fastener.
Applications:	Mounting only on the upper end of the optical components or directly on the connection component.
Function principle:	A modular layout is possible with connection, optical and acoustic components, incandescent lamps and a label panel.
Material:	Enclosure of polyamide
Colour:	Black

Product features

Rated operating voltage:	24 V (AC/DC)
Rated insulation voltage:	250 V AC
Rated impulse withstand voltage, phase to phase:	2500 V AC
Packs of:	1 pc(s).

Weight/pack:	0.1 kg
EAN:	4028177220423
Customs tariff number:	85311095
ETIM 6.0:	EC001261
ETIM 5.0:	EC001261
eCl@ss 8.0/8.1:	27371237
eCl@ss 7.0/7.1:	27371237
eCl@ss 6.0/6.1:	27371237
eCl@ss 5.1/5.1.4:	27371220
Product description (long):	SG Acoustic component, for signal pillar, modular, 24 V AC/DC, 85 dB, max. 25 mA
Approvals	
Approvals:	C-UL UR
Certificates:	EAC
Declarations:	Declaration of conformity