

Rittal – The System.

Faster – better – everywhere.

Security lock – SZ 2418.000

Date : Aug 3, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



Security lock – SZ 2418.000

created: 03.08.2016 on www.rittal.com/com-en



Product description

Description:	Fitted to doors, to protect against contact with live electrical equipment whilst the master switch is ON.
Function principle:	Locks the door when the master switch is ON. Mains power (voltage) is only enabled whilst the door is closed. Monitoring of the lock magnet via an additional closing contact.
Assembly instruction:	In two-door enclosures, the door-operated switch is required for the overlapping door, to indicate "enclosure door closed"
Supply includes:	Lock Actuator Angle bracket Assembly parts
Packs of:	1 pc(s).
EAN:	4028177022690
Customs tariff number:	83015000
eCl@ss 5.1:	27189255
eCl@ss 7.0:	27189266
ETIM 6.0:	EC002626

Rated operating voltage:	24 V (DC)
Power consumption:	With DC: 8 VA
Rated insulation voltage:	400 V AC
Rated impulse withstand voltage, phase to phase:	4000 V AC
Weight/pack:	0.74 kg

Approvals

Approvals:	 CSA (EN)  UL (DE)
-------------------	---

Declarations:	 Declaration of conformity (EN, DE)
----------------------	--

Downloads

Documentation:	 Instructions (EN, DE)
-----------------------	--

CAD drawings:	Request
----------------------	---------

