Rittal - The System.

Faster – better – everywhere.

Interface flaps, modular – SZ 2482.300

Date : Jan 29, 2016



Interface flaps, modular – SZ 2482.300 created: 29.01.2016 on www.rittal.com/com-en



Product description		
Description:	For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed and is therefore protected from ambient influences and unauthorised access.	
Function principle:	The mounting frame has a flap which snaps into position in various stages at opening angles of 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required. All SUB-D interfaces may be rotated while in use	
Material:	Mounting frame and metal flap: Fine die-cast zinc Plastic flap: Polycarbonate (semi-transparent) Lock: Polycarbonate	
Surface finish:	Mounting frame and metal flap: Matt nickel-plated	
Colour:	Lock: RAL 7024 Screw terminals: yellow (RAL 1016)	
Protection category IP to IEC 60 529:	IP 65 with sealed flap and proper assembly	
Packs of:	1 pc(s).	
EAN:	4028177311695	
Customs tariff number:	85369085	
eCl@ss 5.1:	27189238	
eCl@ss 7.0:	27189234	
Rittal 2016		

© Rittal 2016

ETIM 6.0:	EC002625
Product features	
Design:	Mounting frame, single, with plastic flap (semi-transparent) Note: Electrically conductive
Installation options:	As programming interface for controllers As maintenance access for networks For temporary connection of additional equipment For quick connection to existing network structures For programming and maintenance of integral components
Weight/pack:	0.2 kg
Downloads	
Documentation:	🔁 Info sheet (FR, IT, ES, DE, EN, PT)
CAD drawings:	Request

© Rittal 2016 2