

Rittal – The System.

Faster – better – everywhere.

► Interface flaps, modular – SZ 2482.310

Date : Jun 12, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Interface flaps, modular – SZ 2482.310

created: 12.06.2018 on www.rittal.com/com-en



Product description

Design:	Mounting frame, double, with plastic flap (semi-transparent)
Description:	For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed and is therefore protected from ambient influences and unauthorised access.
Function principle:	The mounting frame has a flap which snaps into position in various stages at opening angles of 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required. All SUB-D interfaces may be rotated while in use
Material:	Mounting frame and metal flap: Fine die-cast zinc Plastic flap: Polycarbonate (semi-transparent) Lock: Polycarbonate
Surface finish:	Mounting frame and metal flap: Matt nickel-plated
Colour:	Lock: RAL 7024 Screw terminals: yellow (RAL 1016)
Protection category IP to IEC 60 529:	IP 65 with sealed flap and proper assembly

Product features

Design:	Note: Electrically conductive
Dimensions:	Width: 130 mm Height: 120 mm
Installation options:	As programming interface for controllers

As maintenance access for networks
For temporary connection of additional equipment
For quick connection to existing network structures
For programming and maintenance of integral components

Required mounting cut-out:	Width: 117 mm Height: 91 mm
Packs of:	1 pc(s).
Weight/pack:	0.4 kg
EAN:	4028177490659
Customs tariff number:	85369095
ETIM 6.0:	EC002625
ETIM 5.0:	EC002608
eCl@ss 8.0/8.1:	27189234
eCl@ss 7.0/7.1:	27189234
eCl@ss 6.0/6.1:	27189234
eCl@ss 5.1/5.1.4:	27189238
Product description (long):	SZ Interface flap, modular, mounting frame, double, with plastic flap, semi-transparent
Approvals	
Certificates:	EAC