## Rittal - The System.

Faster – better – everywhere.

Interface flaps, modular – SZ 2482.500

Date : Jan 28, 2016



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Interface flaps, modular – SZ 2482.500 created: 28.01.2016 on www.rittal.com/com-en



Product description	n
Description:	For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed and is therefore protected from ambient influences and unauthorised access.
Function principle:	The mounting frame has a flap which snaps into position in various stages at opening angles o 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required. All SUB-D interfaces may be rotated while in use
Material:	Mounting frame and metal flap: Fine die-cast zinc Plastic flap: Polycarbonate (semi-transparent) Lock: Polycarbonate
Surface finish:	Mounting frame and metal flap: Matt nickel-plated
Colour:	Lock: RAL 7024 Screw terminals: yellow (RAL 1016)
Protection category IP to IEC 60 529:	IP 65 with sealed flap and proper assembly
Packs of:	1 pc(s).
EAN:	4028177490734
Customs tariff number:	85369085
eCl@ss 5.1:	27189238
eCl@ss 7.0:	27189234
© Rittal 2016	

ETIM 6.0:	EC002625
Product features	
Design:	2 x SUB-D9 (jack/pin)
Installation options:	As programming interface for controllers As maintenance access for networks For temporary connection of additional equipment For quick connection to existing network structures For programming and maintenance of integral components
Weight/pack:	0.06 kg
Approvals	
Approvals:	型 C-UR (EN)
Declarations:	Declaration of conformity (EN, DE)
Downloads	
Documentation:	型 Info sheet (FR, IT, ES, DE, EN, PT)
CAD drawings:	Request

© Rittal 2016