

Rittal – The System.

Faster – better – everywhere.

Interface flaps, modular – SZ 2482.540

Date : May 10, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Interface flaps, modular – SZ 2482.540

created: 10.05.2017 on www.rittal.com/com-en



Product description

Description: For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed and is therefore protected from ambient influences and unauthorised access.

Function principle: The mounting frame has a flap which snaps into position in various stages at opening angles of 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required. All SUB-D interfaces may be rotated while in use

Material: Mounting frame and metal flap: Fine die-cast zinc
Plastic flap: Polycarbonate (semi-transparent)
Lock: Polycarbonate

Surface finish: Mounting frame and metal flap: Matt nickel-plated

Colour: Lock: RAL 7024
Screw terminals: yellow (RAL 1016)

Protection category IP to IEC 60 529: IP 65 with sealed flap and proper assembly

Note on Model No.: Conductively connected to mounting frame.

Product features

Design: Note: Conductively connected to mounting frame.

Installation options: As programming interface for controllers
As maintenance access for networks
For temporary connection of additional equipment
For quick connection to existing network structures

For programming and maintenance of integral components

Packs of:	1 pc(s).
Weight/pack:	0.08 kg
Customs tariff number:	85369095
ETIM 6.0:	EC002625
ETIM 5.0:	EC002608
eCl@ss 8.0/8.1:	27189234
eCl@ss 7.0/7.1:	27189234
eCl@ss 6.0/6.1:	27189234
eCl@ss 5.1/5.1.4:	27189238
Product description (long):	SZ Interface flap, modular, interface inserts, 2 x USB A, jack/jack
Approvals	
Approvals:	C-UR
Certificates:	EAC
Declarations:	Declaration of conformity

2017 © Rittal GmbH & Co. KG