Rittal – The System.

Faster – better – everywhere.

LED system light – SZ 2500.100 Date : Sep 14, 2018



ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

LED system light – SZ 2500.100 created: 14.09.2018 on www.rittal.com/com-en



Product description	
Design:	Without socket
Description:	LED system light – the first light especially for enclosures! Highly innovative LED technology for even more light into the very last corner.
Benefits:	Optimum illumination of the entire enclosure Optionally with clip, screw and magnetic attachment A configuration to suit every application
Equipment:	Without socket
Material:	Light body: Extruded aluminium Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS (halogen-free)
Colour:	Enclosure: RAL 7016
Protection category IP to IEC 60 529:	IP 20
Supply includes:	Assembly screws
Product features	
Dimensions:	Width: 262 mm Height: 55 mm Depth: 23 mm
Rated operating voltage:	100 V - 240 V, 1~, 50 Hz/60 Hz

Installation options:	AE, CM, TP: with universal bracket AE: with rail for interior installation
Operating temperature:	Operation (environment): -20°C+55°C
Power consumption:	5 W
Luminous flux:	400 lm
Light colour:	4000 K (neutral white)
Protection category:	ll (all-insulated)
Connection options:	Infeed, 2-pole Through-wiring, 2-pole Door-operated switch
Light – installation type:	Screw-fastening Clip attachment Magnetic attachment (accessory)
Packs of:	1 pc(s).
Weight/pack:	0.29 kg
EAN:	4028177806931
Customs tariff number:	94054099
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Product description (long):	SZ System Light LED, 400 Lumen, L: 262 mm, 100-240 V
Approvals	
Approvals:	ENEC
Certificates:	EAC

Declarations: