Rittal - The System.

Faster – better – everywhere.

LED system light – SZ 2500.310

Date: Dec 19, 2018



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

LED system light – SZ 2500.310

created: 19.12.2018 on www.rittal.com/com-en



| Dana alaa | _4 _1 _ | ! 4! _ | |
|-----------|---------|----------|---|
| Produ | ct ae: | scriptio | n |

Description: LED system light – the first light especially for enclosures! Highly innovative LED

technology for even more light into the very last corner.

Benefits: Optimum illumination of the entire enclosure

Optionally with clip, screw and magnetic attachment

A configuration to suit every application

Equipment: Motion sensor

Socket

90° rotating connector Adjustable light direction Adjustable light distribution

Motion sensor: yes

Material: Light body: Extruded aluminium

Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS (halogen-free)

Colour: Enclosure: RAL 7016

Protection category IP to IEC 60 529:

IP 20

Supply includes: Assembly screws

Product features

Dimensions: Width: 437 mm

Height: 85 mm Depth: 44 mm

© Rittal 2018

| Rated operating voltage: | 100 V - 240 V, 1~, 50 Hz/60 Hz |
|--|---|
| Installation options: | Screw-fasten or clip directly onto the TS/SE section AE, CM, TP: with universal bracket AE: with rail for interior installation |
| Operating temperature: | Operation (environment): -20°C+55°C |
| Power consumption: | 13 W |
| Equipment (electrical): | Jack/socket (type): D, earthing-pin (type F, CEE 7/3) |
| Rated insulation voltage: | 300 V AC |
| Rated impulse withstand voltage, phase to earth: | 2500 V AC |
| Luminous flux: | 1200 lm |
| Light colour: | 4000 K (neutral white) |
| Protection category: | II (all-insulated) |
| Overvoltage category: | II |
| Connection options: | Infeed, 3-pole Through-wiring, 3-pole |
| Light – installation type: | Screw-fastening Clip attachment |
| Packs of: | 1 pc(s). |
| Weight/pack: | 0.7 kg |
| EAN: | 4028177806986 |
| Customs tariff number: | 94054099 |
| ETIM 6.0: | EC000321 |
| ETIM 5.0: | EC000321 |
| | |

© Rittal 2018

eCl@ss 8.0/8.1:

eCl@ss 7.0/7.1:

27189241

27189241

| eCl@ss 6.0/6.1: | 27189241 |
|-----------------------------|--|
| e CI@ss 5.1/5.1.4: | 27189241 |
| Product description (long): | SZ System Light LED, 1200 Lumen, L: 437 mm, 100-240 V, with integral motion detector |
| Approvals | |
| Approvals: | ENEC |
| Certificates: | EAC |
| Declarations: | Declaration of conformity |

© Rittal 2018 3