


# Data sheet

## SO 2847.200



### Main data:

|                               |  |
|-------------------------------|--|
| <b>Model No.:</b>             | SO 2847.200  |
| <b>Designation:</b>           | Base/plinth 200 mm high, for enclosure WxD 600x800 mm, |
| <b>Variant:</b>               | lackiert   |
| <b>Packs of:</b>              | 1 ST   |
| <b>W x H x D:</b>             | 600 mm x 200 mm x 750 mm                               |
| <b>Mounting surface:</b>      | n/a  |
| <b>Volume:</b>                | 35,20 dm <sup>3</sup>                                  |
| <b>Net weight:</b>            | 14,90 kg   |
| <b>EAN:</b>                   | 4028177033306  |
| <b>Customs number:</b>        | n/a  |
| <b>Protection categories:</b> | n/a  |

You can find the product in [Catalogue 32, page 901](#)

### Approbationen:


### Article features:

|                 |  |
|-----------------|--|
| <b>Material</b> | sheet steel  |
|                 | Colour   |
|                 | RAL 7022   |
|                 | Supply includes  |
|                 | 4 corner pieces and removable trim panels for width and depth. |
|                 | Pre-configured.  |
|                 | Dimensions mm W x H x D  |
|                 | for enclosures: 600x200x800 mm                                 |

### Texts for tenders:

# Data sheet

## SO 2847.200



to obtain a greater floor clearance or for cable entry.  
Two-part detachable rear trim panel for cable entry. By folding down the side parts, screw-fastening of bases/plinths and cable routing is possible. System punchings in the side parts for the installation of cable clamp rails and universal attachment.  
Special assembly parts ensure quick and stable mounting with only one screw per side part on the corner piece.  
Captive nuts with earth claws on both sides make baying on the enclosure easier.

**Height: 200 mm**

**Material: sheet steel**

**Surface finish: RAL 7022**

**for enclosure dimensions: W: 600 x D: 800 mm**