

Rittal – The System.

Faster – better – everywhere.

Enclosure heaters with fan – SK 3105.400

Date : Nov 24, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Enclosure heaters with fan – SK 3105.400

created: 24.11.2017 on www.rittal.com/com-en



Product description

Supply includes: PTC heater with fan
Quick-connection terminal
Assembly parts

Note: For precise temperature control inside the enclosure, we recommend the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat. In order to prevent condensation on assemblies, a hygostat is recommended to regulate heating. In larger enclosures, even heat distribution is best achieved by installing several low-output heaters. The installation of heaters is generally advisable, in order to prevent condensation.

Product features

Continuous thermal output at 10°C: 800 W - 870 W
Note: Continuous thermal output with fan

Rated operating voltage: 230 V, 1~, 50 Hz/60 Hz

Dimensions: Width: 103 mm
Height: 200 mm
Depth: 103 mm

Miniature circuit-breaker/fuse: 6 A

Fans pre-integrated: yes

Packs of: 1 pc(s).

Weight/pack: 1.22 kg

EAN:	4028177662889
Customs tariff number:	85162999
ETIM 6.0:	EC000737
ETIM 5.0:	EC000737
eCl@ss 8.0/8.1:	27180710
eCl@ss 7.0/7.1:	27180710
eCl@ss 6.0/6.1:	27180710
eCl@ss 5.1/5.1.4:	27180710
Product description (long):	SK Enclosure heater, 800/870 W, 230 V, 1~, 50/60 Hz, WHD: 103x200x103 mm
Approvals	
Approvals:	Approval overview CSA UR + C-UR VDE
Certificates:	EAC
Declarations:	Declaration of conformity