

Rittal – The System.

Faster – better – everywhere.

Enclosure internal fan for TS – SK 3108.100

Date : May 16, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Enclosure internal fan for TS – SK 3108.100

created: 16.05.2017 on www.rittal.com/com-en



Product description

Description: To prevent hot-spots and support the air routing of active enclosure climate control components. Adjustable in two axes. Attached to the TS 8 frame section. Several fans may be cascaded using the quick-release clamping strip.

Supply includes: Complete unit with radial fan ready for connection
Snap-on pivot device
Assembly parts

Product features

Air throughput (unimpeded air flow): 160 m³/h

Rated operating voltage: 230 V, 1~, 50 Hz/60 Hz

**Power consumption
Pel:** At 50 Hz: 19 W
At 60 Hz: 18 W

Rated current (max.): At 50 Hz: 0.12 A
At 60 Hz: 0.11 A

Packs of: 1 pc(s).

Weight/pack: 1.14 kg

Customs tariff number: 84145100

ETIM 6.0: EC000320

ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705
Product description (long):	SK Enclosure internal fan, 160 m ³ /h, 230 V, 1~, 50/60 Hz
Approvals	
Approvals:	Approval overview
Certificates:	EAC

2017 © Rittal GmbH & Co. KG