

Rittal – The System.

Faster – better – everywhere.

Hygrostat – SK 3118.000

Date : Mar 2, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hygrostat – SK 3118.000

created : 02.03.2014 on www.rittal.com/com-en



Product description

Description:

- The hygrostat switches on the heater and/or fan when a preset relative humidity in the enclosure is exceeded. In this way, the relative humidity is raised above the dew point, and condensation on assemblies or electronic components is avoided.

Technical specifications:

- Contact population: Single-pole change-over contact as a quick-break contact.
- Permissible contact load: AC ~ 5 (0,2) 1) A DC = max. 20 W (1) = inductive load at $\cos j = 0.6$
- Setting range: 50 – 100 % relative humidity
- Switching difference: approx. 4%
- Time-saving connection technique using a terminal strip with a screw connection from the outside.
- Flexible mounting on a vertical or horizontal 35 mm support rail to EN 50 022, and snap fastening in the TS/SE enclosure section or on the mounting plate using the supplied adaptor

Packs of:

- 1 pc(s).

EAN:

- 4028177036734

Customs tariff number:

- 90321089

Product features

Dimensions:


- Width: 71 mm
- Height: 71 mm
- Depth: 33.5 mm

Weight:

- 100 g


Approvals

Declarations:


-  [Declaration of conformity \(EN, DE\)](#)

Downloads

Data sheets:

-  [Technical system catalogue \(DE\)](#)

Documentation:

-  [Instructions \(SE, DE, ES, EN, FR, NL, IT\)](#)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP