

Rittal – The System.

Faster – better – everywhere.

Roof-mounted fan, roof vent – SK 3139.100

Date : Aug 14, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Roof-mounted fan, roof vent – SK 3139.100

created: 14.08.2017 on www.rittal.com/com-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 21 without filter mat
IP 55 including filter mat

**Protection category
NEMA:** NEMA 12

Supply includes: Complete unit ready to install, including filter mat

Note: For energy-efficient operation of the fans, we recommend the use of thermostats or temperature displays

Product features

**Air throughput
(unimpeded air flow):** 500 m³/h

**Air throughput,
unimpeded air flow
(without filter mats):** 500 m³/h / 525 m³/h

**Air throughput,
unimpeded air flow
(with filter mats):** 417 m³/h / 446 m³/h

**Rated operating
voltage:** 230 V, 1~, 50 Hz/60 Hz

Dimensions: Width: 400 mm
Height: 133 mm
Depth: 400 mm

Required mounting cut-out:	Width: 258 mm Depth: 258 mm
Installation depth:	34.6 mm
Temperature range:	Bearing: -40°C...+70°C Operation (environment): -30°C...+55°C
Power consumption Pel:	At 50 Hz: 50 W At 60 Hz: 62 W
Rated current (max.):	At 50 Hz: 0.22 A At 60 Hz: 0.27 A
Miniature circuit-breaker/fuse:	6 A
Diagonal fan:	Radial, capacitor motor
Packs of:	1 pc(s).
EAN:	4028177709171
Customs tariff number:	84145100
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180707
Product description (long):	SK TopTherm roof-mounted fan, 500 m ³ /h, 230 V, 1~, 50/60 Hz

Approvals

Approvals:	Approval overview CSA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity

