Rittal – The System.

Faster – better – everywhere.

TopTherm fan-and-filter units – SK 3237.110

Date : Jun 26, 2017

TopTherm fan-and-filter units – SK 3237.110

created: 26.06.2017 build on www.rittal.com/uk-en

Product description

Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 54 NEMA 12 With hose-proof hood: IP 56 With hose-proof hood: NEMA 3 With hose-proof hood: NEMA 3R
Supply includes:	Complete unit ready to install, including filter mat
Note:	With the fan-and-filter unit 3237.XXX, electrical connection is made via two single wires on the unit; for all other fan-and-filter units, a screwless spring terminal is used.

Product features

Air throughput (unimpeded air flow):	At 50 Hz: 20 m³/h At 60 Hz: 25 m³/h
Air throughput with outlet filter including standard filter mat:	Number of outlet filters: 1 Model No. of outlet filter: SK 3237.200 At 50 Hz: 15 m³/h At 60 Hz: 18 m³/h
Rated operating voltage:	115 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 116.5 mm Height: 116.5 mm
Required mounting cut-out:	Width: 92 mm Height: 92 mm

Build depth:	16 mm
Installation depth:	43 mm
Temperature range:	Bearing: -30°C...+70°C Operation (environment): -15°C...+55°C
Power consumption Pel:	At 50 Hz: 11 W At 60 Hz: 9 W
Rated current (max.):	At 50 Hz: 0.12 A At 60 Hz: 0.1 A
Miniature circuit-breaker/fuse:	2 A
Noise level:	At 50 Hz: 38 dB(A) At 60 Hz: 43 dB(A)
Diagonal fan:	Axial, self-starting shaded pole motor
Packs of:	1 pc(s).
Weight/pack:	0.48 kg
EAN:	4028177651593
Customs tariff number:	84145100
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705
Product description (long):	SK TopTherm fan-and-filter unit, 20/25 m³/h, 115 V, 1~, 50/60 Hz, WH: 116.5x116.5 mm

Approvals

Approvals:	Approval overview C-UR

	CSA UR UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity

2017 © Rittal Ltd UK