

Rittal – The System.

Faster – better – everywhere.

► TopTherm fan-and-filter units – SK 3238.110

Date : Jul 3, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3238.110

created: 03.07.2017 on www.rittal.com/com-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54
NEMA 12
With hose-proof hood: IP 56
With hose-proof hood: NEMA 3
With hose-proof hood: NEMA 3R
With hose-proof hood: NEMA 4
With hose-proof hood: NEMA 4X
With fine filter mat or hose-proof hood: IP 54
With fine filter mat or hose-proof hood: NEMA 12

Supply includes: Complete unit ready to install, including filter mat

Note: With the fan-and-filter unit 3237.XXX, electrical connection is made via two single wires on the unit; for all other fan-and-filter units, a screwless spring terminal is used.

Product features

**Air throughput
(unimpeded air flow):** At 50 Hz: 55 m³/h
At 60 Hz: 66 m³/h

**Air throughput with
outlet filter including
standard filter mat:** Number of outlet filters: 1
Number of outlet filters: 2
Model No. of outlet filter: SK 3238.200
Model No. of outlet filter: SK 3238.200
At 50 Hz: 43 m³/h
At 50 Hz: 46 m³/h
At 60 Hz: 50 m³/h
At 60 Hz: 56 m³/h

Rated operating 115 V, 1~, 50 Hz/60 Hz

voltage:	
Dimensions:	Width: 148.5 mm Height: 148.5 mm
Required mounting cut-out:	Width: 124 mm Height: 124 mm
Build depth:	16 mm
Installation depth:	58.5 mm
Temperature range:	Bearing: -30°C...+70°C Operation (environment): -10°C...+55°C
Power consumption Pel:	At 50 Hz: 19 W At 60 Hz: 18 W
Rated current (max.):	At 50 Hz: 0.24 A At 60 Hz: 0.22 A
Miniature circuit-breaker/fuse:	2 A
Noise level:	At 50 Hz: 46 dB(A) At 60 Hz: 49 dB(A)
Diagonal fan:	Diagonal, self-starting shaded pole motor
Packs of:	1 pc(s).
Weight/pack:	0.8 kg
EAN:	4028177651715
Customs tariff number:	84145100
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705
Product description	SK TopTherm fan-and-filter unit, 55/66 m ³ /h, 115 V, 1~, 50/60 Hz, WH: 148.5x148.5 mm

(long):

Approvals

Approvals:	Approval overview C-UR CSA UR UR + C-UR
-------------------	---

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity
----------------------	---------------------------

2017 © Rittal GmbH & Co. KG