

Rittal – The System.

Faster – better – worldwide.

► TopTherm fan-and-filter units – SK 3239.124

Date : Oct 27, 2013

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3239.124

created : 27.10.2013 on www.rittal.com/com-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54
With hose-proof hood: IP 56
With fine filter mat or hose-proof hood: IP 55

Supply includes: Complete unit ready to install, including filter mat

Note: For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat

Packs of: 1 pc(s).

EAN: 4028177651845

**Customs tariff
number:** 84145100

Product features






**Air throughput
(unimpeded air flow):** With DC: 105 m³/h

**Air throughput with
outlet filter including
standard filter mat:** Number of outlet filters: 1
2
1
Model No. of outlet filter :
SK 3239.200
SK 3239.200
SK 3240.200
With DC: 87 m³/h
93 m³/h









98 m³/h

Rated operating voltage:	24 V DC/-/-
Dimensions:	Width: 204 mm Height: 204 mm
Required mounting cut-out:	Width: 177 mm Height: 177 mm
Build depth:	24 mm
Installation depth:	90 mm
Temperature ranges:	Bearing: - 30 °C/+ 70 °C Operation (environment): - 15 °C - + 55 °C
Power consumption Pel:	With DC: 5.5 W
Rated current (max.):	With DC: 0.23 A
Pre-fuse:	Miniature circuit-breaker/fuse: 2 A
Noise level:	With DC: 46 dB(A)
Diagonal fan:	Diagonal, DC motor




Approvals

Certificates	Sorry, there is currently no information available
Declarations	 Declaration of conformity (EN, DE)
Approvals	 CSA (EN)  UR (EN)  C-UR (EN)  Approval overview (EN)

Downloads / CAD

Documentation	 Instructions (EN)  Instructions (DE)  Instructions (ES)  Instructions (FR)  Instructions (IT)  Instructions (JP)  Instructions (NL)  Instructions (SV)
Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available

Data sheets

-  Technical System Catalogue (DE)
-  Performance diagrams (DE)
-  Technical data sheet (EN)

CAD-Drawing

Request

Please note that there are the following alternative products:



TopTherm Filterlüfter EMV

Rittal – The System.

Faster – better – worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postbox 1662 · D-35726 Herborn
Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

