

Rittal – The System.

Faster – better – worldwide.

► TopTherm fan-and-filter units – SK 3240.110

Date : Jan 13, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3240.110

created : 13.01.2014 on www.rittal.com/com-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54
With hose-proof hood: IP 56
With fine filter mat or hose-proof hood: IP 55

Supply includes: Complete unit ready to install, including filter mat

Note: For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat

Packs of: 1 pc(s).

EAN: 4028177651951

**Customs tariff
number:** 84145100

Product features






**Air throughput
(unimpeded air flow):** At 50 Hz: 180 m³/h
At 60 Hz: 160 m³/h

**Air throughput with
outlet filter including
standard filter mat:** Number of outlet filters: 1
2
1
Model No. of outlet filter :
SK 3240.200
SK 3240.200
SK 3243.200
At 50 Hz: 138 m³/h







165 m³/h
165 m³/h
At 60 Hz: 115 m³/h
140 m³/h
140 m³/h

Rated operating voltage:	115 V AC/1~/50 Hz 115 V AC/1~/60 Hz
Dimensions:	Width: 255 mm Height: 255 mm
Required mounting cut-out:	Width: 224 mm Height: 224 mm
Build depth:	25 mm
Installation depth:	107 mm
Temperature range:	Bearing: - 30 °C/+ 70 °C Operation (environment): - 30 °C - + 55 °C
Power consumption Pel:	At 50 Hz: 35 W At 60 Hz: 34 W
Rated current (max.):	At 50 Hz: 0.42 A At 60 Hz: 0.38 A
Pre-fuse:	Miniature circuit-breaker/fuse: 4 A
Noise level:	At 50 Hz: 51 dB(A) At 60 Hz: 46 dB(A)
Diagonal fan:	Diagonal, self-starting shaded pole motor



Approvals

Certificates	Sorry, there is currently no information available
Declarations	 Declaration of conformity (EN, DE)
Approvals	 CSA (EN)  UR (EN)  C-UR (EN)  Approval overview (EN)

Downloads / CAD

Documentation	 Instructions (EN)  Instructions (DE)  Instructions (ES)  Instructions (FR)  Instructions (IT)  Instructions (JP)
----------------------	--

 Instructions (NL)
 Instructions (SV)

Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available
Data sheets	 Technical System Catalogue (DE)  Performance diagrams (DE)
CAD-Drawing	Request
Treiber/Software	Sorry, there is currently no information available

Please note that there are the following alternative products:



TopTherm Filterlüfter EMV

Rittal – The System.

Faster – better – worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postbox 1662 · D-35726 Herborn
Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

