

Rittal – The System.

Faster – better – worldwide.

► TopTherm fan-and-filter units – SK 3240.600

Date : Oct 28, 2013

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units EMC – SK 3240.600

created : 28.10.2013 on www.rittal.com/com-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54
With hose-proof hood: IP 56
With fine filter mat or hose-proof hood: IP 55

Supply includes: Complete unit ready to install, including filter mat

Note: For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat

Packs of: 1 pc(s).

EAN: 4028177652453

**Customs tariff
number:** 84145100

Product features






**Air throughput
(unimpeded air flow):** At 50 Hz: 180 m³/h
At 60 Hz: 160 m³/h

**Air throughput with
outlet filter including
standard filter mat:** Number of outlet filters: 1
2
1
Model No. of outlet filter :
SK 3240.060
SK 3240.060
SK 3243.060
At 50 Hz: 138 m³/h

165 m³/h
165 m³/h
At 60 Hz: 115 m³/h
140 m³/h
140 m³/h







Rated operating voltage:	230 V AC/1~/50 Hz 230 V AC/1~/60 Hz
Dimensions:	Width: 255 mm Height: 255 mm
Required mounting cut-out:	Width: 224 mm Height: 224 mm
Build depth:	25 mm
Installation depth:	107 mm
Temperature ranges:	Bearing: - 30 °C/+ 70 °C Operation (environment): - 30 °C - + 55 °C
EMC version:	x
Power consumption Pel:	At 50 Hz: 35 W At 60 Hz: 34 W
Rated current (max.):	At 50 Hz: 0.21 A At 60 Hz: 0.19 A
Pre-fuse:	Miniature circuit-breaker/fuse: 2 A
Noise level:	At 50 Hz: 51 dB(A) At 60 Hz: 46 dB(A)
Diagonal fan:	Diagonal, self-starting shaded pole motor




Approvals

Certificates	Sorry, there is currently no information available
Declarations	 Declaration of conformity (EN, DE)
Approvals	 CSA (EN)  UR (EN)  C-UR (EN)  Approval overview (EN)

Downloads / CAD

Documentation	 Instructions (EN)  Instructions (DE)
----------------------	--

-  Instructions (ES)
-  Instructions (FR)
-  Instructions (IT)
-  Instructions (JP)
-  Instructions (NL)
-  Instructions (SV)

Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available
Data sheets	<ul style="list-style-type: none">  Technical System Catalogue (DE)  Performance diagrams (DE)  Technical data sheet (EN)
CAD-Drawing	Request

Please note that there are the following alternative products:



TopTherm Filterlüfter

Weitere Informationen zu diesem Produkt

» www.rittal.com/com-en/TopTherm_fan_and_filter_units



TopTherm Filterlüfter

Rittal – The System.

Faster – better – worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postbox 1662 · D-35726 Herborn
Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

