

Rittal – The System.

Faster – better – everywhere.

► TopTherm fan-and-filter units – SK 3241.124

Date : Jun 16, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3241.124

created : 16.06.2015 on www.rittal.com/com-en



Product description

Colour: RAL 7035

Supply includes: Complete unit ready to install, including filter mat

Note: For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat

Packs of: 1 pc(s).

EAN: 4028177652019

Customs tariff number: 84145100

eCl@ss 5.1: 27180705

eCl@ss 7.0: 27180716

Product features

Air throughput (unimpeded air flow): With DC: 230 m³/h

Rated operating voltage: 24 V (DC)
Note for voltage: (DC)

Dimensions: Width: 255 mm
Height: 255 mm

Required mounting cut-out:	Width: 224 mm Height: 224 mm
Build depth:	25 mm
Installation depth:	107 mm
Temperature range:	Bearing: -30°C...+70°C Operation (environment): -30°C...+55°C
Power consumption Pel:	With DC: 19 W
Rated current (max.):	With DC: 0.8 A
Pre-fuse:	Miniature circuit-breaker/fuse: 2 A
Noise level:	With DC: 54 dB(A)
Diagonal fan:	Diagonal, DC motor
Weight/PU:	2.04 kg

Approvals

Approvals:	Approval overview (EN) C-UR (EN) CSA (EN) UR (EN) UR + C-UR (EN)
Declarations:	Declaration of conformity (DE)

Downloads

Data sheets:	Performance diagrams DE Technical details EN Technical system catalogue (DE)
Documentation:	Instructions EN
Specialist literature:	The Rittal technology library EN
CAD drawings:	Request

Please note that there are the following alternative products:



TopTherm fan-and-filter units EMC