

# Rittal – The System.

Faster – better – everywhere.

## ► TopTherm fan-and-filter units with EC technology – SK 3243.500

Date : Mar 16, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TopTherm fan-and-filter units with EC technology – SK 3243.500

created: 16.03.2021 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

|  |  |
|--|--|
| <b>Protection category IP to IEC 60 529:</b> | IP 54<br>with standard filter and additional fine filter mat: IP 55<br>with standard filter and hose-proof hood: IP 56 |
|--|--|

|                                  |  |
|----------------------------------|--|
| <b>Protection category NEMA:</b> | Type 12<br>with standard filter and additional fine filter mat: Type 12<br>with standard filter and hose-proof hood: Type 3, 3R, 4, 4X |
|----------------------------------|--|

|                         |  |
|-------------------------|--|
| <b>Supply includes:</b> | Complete unit ready to install, including filter mat |
|-------------------------|--|

|              |   |
|--------------|---|
| <b>Note:</b> | For even more efficient operation or for monitoring the fan-and-filter units, we recommend the use of an EC speed control for EC fan-and-filter units |
|--------------|---|

## Product description

|   |  |
|---|--|
| <b>Air throughput (unimpeded air flow):</b> | At 50 Hz: 550 m <sup>3</sup> /h<br>At 60 Hz: 550 m <sup>3</sup> /h |
|---|--|

|  |  |
|--|--|
| <b>Air throughput with outlet filter including standard filter mat (quantity x order number, output 50/60 Hz):</b> | 1 x 3243200: 465 m <sup>3</sup> /h<br>2 x 3243200: 508 m <sup>3</sup> /h |
|--|--|

|                           |     |
|---------------------------|-----|
| <b>Control interface:</b> | yes |
|---------------------------|-----|

|                                 |                                |
|---------------------------------|--------------------------------|
| <b>Rated operating voltage:</b> | 200 V - 240 V, 1~, 50 Hz/60 Hz |
|---------------------------------|--------------------------------|

|                    |               |
|--------------------|---------------|
| <b>Dimensions:</b> | Width: 323 mm |
|--------------------|---------------|

Height: 323 mm

|  |  |
|--|--|
| <b>Required mounting cut-out:</b>        | Width: 292 mm<br>Height: 292 mm  |
| <b>Build depth:</b>                      | 25 mm  |
| <b>Installation depth:</b>               | 118.5 mm   |
| <b>Temperature range:</b>                | Bearing: -25 °C...+70 °C<br>Operation (environment): -25 °C...+55 °C                             |
| <b>Power consumption P<sub>el</sub>:</b> | At 50 Hz: 51 W<br>At 60 Hz: 51 W   |
| <b>Rated current max.:</b>               | At 50 Hz: 0.5 A<br>At 60 Hz: 0.5 A   |
| <b>Miniature circuit-breaker/fuse:</b>   | 6 A  |
| <b>Service life:</b>                     | 65000 h  |
| <b>Noise level:</b>                      | At 50 Hz: 63 dB(A)<br>At 60 Hz: 63 dB(A)   |
| <b>Colour:</b>                           | RAL 7035   |
| <b>Fan:</b>                              | Diagonal, EC motor   |
| <b>eCl@ss 8.0/8.1:</b>                   | 27180716   |
| <b>Packs of:</b>                         | 1 pc(s).   |
| <b>Weight/pack:</b>                      | 2.92 kg  |
| <b>EAN:</b>                              | 4028177652156  |
| <b>Customs tariff number:</b>            | 84145915   |
| <b>ETIM 7.0:</b>                         | EC000320   |
| <b>ETIM 6.0:</b>                         | EC000320   |
| <b>eCl@ss 8.0/8.1:</b>                   | 27180716   |
| <b>eCl@ss 6.0/6.1:</b>                   | 27180716   |
| <b>Product description:</b>              | SK fan and filter units TopTherm, 550 m <sup>3</sup> /h, 200-240 V, 1~, 50/60 Hz, WHD: 323 x 323 |

## Approvals

|                   |   |
|-------------------|---|
| <b>Approvals:</b> | Approval overview<br>CCC exception letter<br>CSA<br>UL + C-UL - FTTA<br>UR + C-UR |
|-------------------|---|

|                      |     |
|----------------------|-----|
| <b>Certificates:</b> | EAC |
|----------------------|-----|

|                      |                           |
|----------------------|---------------------------|
| <b>Declarations:</b> | Declaration of conformity |
|----------------------|---------------------------|