

Data sheet

SK 3302.300



Main data:

Model No.:	SK 3302.300
Designation:	TopTherm PLUS Mini cooling unit, 300 W, horiz. format, wall-m., RiNano coating, basic controller, 230 V, 50/60 Hz
Variant:	Basiscontroller
Packs of:	1 ST
W x H x D:	525 mm x 340 mm x 153 mm
Mounting surface:	n/a
Volume:	30,80 dm ³
Net weight:	14,92 kg
EAN:	4028177429796
Customs number:	84158200
Protection categories:	n/a

You can find the product in [Catalogue 32, page 642](#)

Approbationen:

CE	3 238 305
CSA	1672554
CUR	SA 8250
GS	44 315 09 368698-002
UR	SA 8250

Article features:

Prefuse T / A
10 A/ 10 A
Rated operating voltage V/Hz
230, 50/60
Rated current max. A

Data sheet

SK 3302.300



1.6 A/1.7 A

Refrigerant

R134a, 100 g

Temperature range °C

Temperature range: + 20°C to + 55°C (Setting range + 30°C to + 55°C)

Technical specifications

Dimensions mm:

Width: 525 mm

Height: 340 mm

Depth: 153 mm

Start-up current: 4.3 A/5.3 A

Power consumption P_{el} to DIN 3168:

L 35 L 35: 285 W/300 W

L 35 L 45: 320 W/340 W

Refrigeration factor: L 35 L 35: 1.1

Permissible operating pressure p. max.: 25 bar

Duty cycle: 100 %

Type of connection: Plug-in terminal strip

Temperature control: Basic controller

Air throughput, unimpeded air flow / m³/h

Air throughput of fans: (unimpeded air flow):

External circuit: 345 m³/h

Internal circuit: 310 m³/h

Useful cooling output L35L35 50 Hz / W
300 W

Useful cooling output L35L35 60 Hz / W
320 W

Useful cooling output L35L45 50 Hz / W

Data sheet

SK 3302.300



150 W
Useful cooling output L35L45 60 Hz / W
160 W
Weight / kg
13.00 kg
Colour
RAL 7035
Supply includes
Fully wired ready for connection, including drilling
template and

assembly parts.
Product notes
Special voltages available on request. We reserve the right
to make

technical modifications.

Texts for tenders:

Rittal TopTherm PLUS wall-mount. horizontal cooling unit
with RiNano coating
Useful cooling output to DIN 3168 L35 L35 300/320 W

Rated operating voltage: 230V, 1 ~, 50/60 Hz

Power consumption Pel to DIN 3168 L35 L35,285/300 W
Dimensions W x H x D [mm] 525 x 340 x 153

Refrigerant: R 134 a

Temperature range: 20°C - 55°C (Setting range +30°C to +55°C)

Temperature control and monitoring via basic controller
with floating fault signal contact and connection
for door operated switch

Factory setting: 35°C

Connection via plug-in terminal strips

Data sheet

SK 3302.300



External circuit IP 34 / Internal circuit IP 54

Weight: 13 kg
Colour RAL 7035.