

Rittal – The System.

Faster – better – everywhere.

► **TopTherm wall-mounted cooling units "Blue e", NEMA 4X Total cooling output 0.50 – 2.50 kW – SK 3303.504**

Date : Jun 27, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Spare parts - TopTherm wall-mounted cooling units "Blue e", NEMA 4X Total cooling output 0.50 – 2.50 kW – SK 3303.504

created: 27.06.2017 on www.rittal.com/com-en



Product description

Material:	Stainless steel 1.4404 (AISI 316L)
Protection category NEMA:	NEMA 4X
Supply includes:	Nano-coated condenser Integral electric condensate evaporation Fully wired ready for connection (plug-in terminal strip) Drilling template Assembly parts
Note:	3303.XXX without integral condensate evaporation
Note on Model No.:	without integral condensate evaporation

Product features

Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 0.55 kW L 35 L 35 at 60 Hz: 0.66 kW L 35 L 50 at 50 Hz: 0.33 kW L 35 L 50 at 60 Hz: 0.4 kW
Air throughput (unimpeded air flow):	External circuit: 315 m ³ /h Internal circuit: 265 m ³ /h
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz

Dimensions:	Width: 285 mm Height: 620 mm Depth: 298 mm
Temperature control:	e-Comfort controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+50°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 170 g
Power consumption Pel:	L 35 L 35 at 50 Hz: 0.39 kW L 35 L 35 at 60 Hz: 0.41 kW L 35 L 50 at 50 Hz: 0.42 kW L 35 L 50 at 60 Hz: 0.39 kW
Rated current (max.):	At 50 Hz: 2.6 A At 60 Hz: 2.6 A
Start-up current max.:	At 50 Hz: 5.1 A At 60 Hz: 6.4 A
Miniature circuit-breaker/fuse:	10 A
Permissible operating pressure (p. max.):	28 bar
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	1.4
Weight/pack:	25 kg
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 6.0/6.1:	27180704
Product description (long):	SK Blue e cooling unit, Wall-mounted, NEMA 4X, 0.55 kW, 230 V, 1~, 50/60 Hz, Stainless steel, WHD: 285x620x298 mm

Approvals

Approvals:	CSA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation

