

Rittal – The System.

Faster – better – everywhere.

► **TopTherm wall-mounted cooling units "Blue e", NEMA 4X Total cooling output 0.50 – 2.50 kW – SK 3304.504**

Date : Jul 17, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Spare parts - TopTherm wall-mounted cooling units "Blue e", NEMA 4X Total cooling output 0.50 – 2.50 kW – SK 3304.504

created: 17.07.2017 on www.rittal.com/com-en



Product description

Material: Stainless steel 1.4404 (AISI 316L)

Protection category NEMA: NEMA 4X

Supply includes: Nano-coated condenser
Integral electric condensate evaporation
Fully wired ready for connection (plug-in terminal strip)
Drilling template
Assembly parts

Note: 3303.XXX without integral condensate evaporation

Product features

Total cooling output to DIN EN 14511: L 35 L 35 at 50 Hz: 1.1 kW
L 35 L 35 at 60 Hz: 1.25 kW
L 35 L 50 at 50 Hz: 0.91 kW
L 35 L 50 at 60 Hz: 0.9 kW

Air throughput (unimpeded air flow): External circuit: 900 m³/h
Internal circuit: 600 m³/h

Rated operating voltage: 230 V, 1~, 50 Hz/60 Hz

Dimensions: Width: 405 mm
Height: 1020 mm

Depth: 358 mm

Temperature control:	e-Comfort controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+50°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 325 g
Power consumption Pel:	L 35 L 35 at 50 Hz: 0.64 kW L 35 L 35 at 60 Hz: 0.68 kW L 35 L 50 at 50 Hz: 0.71 kW L 35 L 50 at 60 Hz: 0.81 kW
Rated current (max.):	At 50 Hz: 3.9 A At 60 Hz: 4.3 A
Start-up current max.:	At 50 Hz: 12 A At 60 Hz: 14 A
Miniature circuit-breaker/fuse:	10 A
Permissible operating pressure (p. max.):	28 bar
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	1.83
Packs of:	1 pc(s).
Weight/pack:	49 kg
EAN:	4028177384293
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704
Product description	SK Blue e cooling unit, Wall-mounted, NEMA 4X, 1.1 kW, 230 V, 1~, 50/60 Hz, Stainless

(long): steel

Approvals

Approvals: CSA
UR + C-UR

Certificates: EAC

Declarations: Declaration of conformity
Declaration of conformity - F-gas regulation

2017 © Rittal GmbH & Co. KG