

Data sheet

SK 3359.540



Main data:

Model No.:	SK 3359.540
Designation:	Rittal TopTherm PLUS Midi cooling unit, roof-mounted, 750 W,, comfort controller, 400 V, 2~, 50/60 Hz
Variant:	Comfortcontroller
Packs of:	1 ST
W x H x D:	597 mm x 415 mm x 375 mm
Mounting surface:	n/a
Volume:	172,83 dm ³
Net weight:	38,95 kg
EAN:	4028177433717
Customs number:	84158200
Protection categories:	n/a

Approbationen:

CE	3 237 305
CUR	SA 8250
GS	44 315 09 368698
UR	SA 8250

Article features:

Pre-fuse T / A
10 A/ 10 A
Rated operating voltage V/Hz
400, 2 ~, 50/60
Rated current max. A
1.7 A/2.2 A

Data sheet

SK 3359.540



Refrigerant
R134a, 300 g
Temperature range °C
Temperature and setting range: + 20°C to + 55°C
Technical specifications
Dimensions mm:
Width: 597 mm
Height: 415 mm
Depth: 375 mm
Start-up current: 5.8 A/6.2 A
Power consumption P_{el} to DIN 3168:
L 35 L 35: 420 W/535 W
L 35 L 50: 500 W/615 W
Refrigeration factor: L 35 L 35: 1.8
Permissible operation pressure p. max.: 25 bar
Duty cycle: 100 %
Type of connections: Pluggable terminal strip
Temperature control: Comfort controller
(factory setting + 35 ° C)
Air throughput, unimpeded air flow / m³/h
Air throughput of fans (unimpeded air flow):
External circuit: 910 m³/h
Internal circuit: 440 m³/h
Useful cooling output L35L35 50 Hz / W
750 W
Useful cooling output L35L35 60 Hz / W
810 W
Useful cooling output L35L50 50 Hz / W

Data sheet

SK 3359.540



545 W

Useful cooling output L35L50 60 Hz / W

590 W

Weight / kg

37 kg

Colour

RAL 7035

Supply includes

Fully wired ready for connection, including drilling
template and

assembly parts.

Product notes

Cooling units with Comfort controller may be integrated
e.g. into

superordinate remote monitoring systems by way of an
optional interface

board SK 3124.200 (RS 232, RS 485, RS 422 and PIC
interface).