

Data sheet

SK 3361.500



Main data:

Model No.:	SK 3361.500
Designation:	TopTherm Blue e Midi cooling unit, wall-mounted, 750 W, RiNano coating, comfort controller, 230 V, 50/60 Hz
Variant:	Comfortcontroller, Comfortcontroller, Comfortcontroller, Comfortcontroller, Comfor
Packs of:	1 ST
W x H x D:	280 mm x 550 mm x 280 mm
Mounting surface:	n/a
Volume:	58,74 dm ³
Net weight:	22,23 kg
EAN:	4028177429536
Customs number:	84158200
Protection categories:	n/a

Approbationen:

CE	3 238 305
CE	3 409 810
CSA	1745342
GS	44 315 09 368698-002
UR	SA 8250

Article features:

Pre-fuse T / A
10 A/ 10 A
Rated operating voltage V/Hz
230, 50/60
Rated current max. A

Data sheet

SK 3361.500



2.3 A/2.4 A

Refrigerant

R134a

Temperature range °C

Temperature and setting range: + 20°C to + 52°C

Technical specifications

Dimensions mm:

Width: 280 mm

Height: 550 mm

Depth: 206 mm

Start-up current: 5.6 A/5.6 A

Power consumption P_{el} to DIN 3168:

L 35 L 35: 420 W/450 W

L 35 L 50: 480 W/510 W

Refrigeration factor: L 35 L 35: 1.5

Permissible operating pressure p. max.: 28 bar

Duty cycle: 100 %

Type of connection: Plug-in terminal strip

Temperature control: Comfort controller (factory setting + 35 ° C)

Air throughput, unimpeded air flow / m³/h

Air throughput of fans (unimpeded air flow):

External circuit: 480 m³/h

Internal circuit: 600 m³/h

Useful cooling output L35L35 50 Hz / W
750 W

Useful cooling output L35L35 60 Hz / W
790 W

Useful cooling output L35L50 50 Hz / W

Data sheet

SK 3361.500



570 W
Useful cooling output L35L50 60 Hz / W
570 W
Weight / kg
22 kg
Colour
RAL 7035
Supply includes
Fully wired ready for connection, including drilling
template and

assembly parts.
Product notes
Cooling units with Comfort controller may be integrated
e.g. into

superordinate remote monitoring systems by way of an
optional interface

board SK 3124.200 (RS 232, RS 485, RS 422 and PLC
interface).

Texts for tenders:

Rittal TopTherm Blue e wall-mounted cooling unit
with RiNano coating
Useful cooling output to DIN 3168 L35 L35, 750/790 W

Rated operating voltage: 230 V, 1 ~, 50/60 Hz

Power consumption Pel to DIN 3168 L35 L35, 420/450 W
Dimensions W x H x D [mm] 280 x 550 x 206

Refrigerant: R 134 a

Temperature range: 20°C - 55°C²⁾

Temperature control and monitoring via comfort
controller with two cooling and two signal contacts
and connection for door-operated switch

FRIEDEMUND LOHMEYER GROUP

Factory setting: 35°C

Data sheet

SK 3361.500



Protection category to EN 60 529/10.91
External circuit IP 34 / Internal circuit IP 54

Weight: 22 kg

Colour RAL 7035.

²)Tu max. = 52°C/60 Hz