

Data sheet

SK 3382.500



Main data:

Model No.:	SK 3382.500
Designation:	TopTherm Blue e roof-mount. cooling unit, 500 W, comfort control., 230 V, 50/60Hz, RiNano coating / condensate evaporation
Variant:	Comfortcontroller, Comfortcontroller, Comfortcontroller, Comfortcontroller, Comfor
Packs of:	1 ST
W x H x D:	595 mm x 415 mm x 375 mm
Mounting surface:	n/a
Volume:	162,67 dm ³
Net weight:	28,50 kg
EAN:	4028177323162
Customs number:	84158200
Protection categories:	n/a

Approbationen:

CE	3 237 305
CSA	1768404
CUR	SA 8250
GS	44 315 09 368698
UL	Bestätigung Type 12
UR	SA 8250

Article features:

Pre-fuse T 50 Hz / A
10.0
Rated current 60 Hz / A
2.9

Data sheet

SK 3382.500



Operating pressure p. max
25 bar
Power consumption L35L35 50 Hz / W
302 W
Refrigerant
R134a
Power consumption L35L50 50 Hz / W
342 W
Pre-fuse T 60 Hz / A
10.0
Power consumption L35L50 60 Hz / W
402 W
Rated current 50 Hz / A
2.7
Useful cooling output L35L50 50 Hz / W
373 W
Useful cooling output L35L35 50 Hz / W
500 W
Start-up current 60 Hz / A
10.2 A
Air throughput, internal circuit / m³/h
440 m³/h
Supply includes
Fully wired ready for connection, including drilling
template, eyebolt,

assembly parts and multilingual assembly instructions.
Weight / kg
30 kg
Start-up current 50 Hz / A

Data sheet

SK 3382.500



9.2 A

Product notes

Special voltages available on request. We reserve the right to make

technical modifications.

Rated operating voltage V/Hz

230, 50/60

Protection category external circuit

IP 34

Protection category internal circuit

IP 54

Duty cycle

100 %

Colour

RAL 7035

Air throughput external circuit / m³/h

910 m³/h

Temperature range °C

+ 20 ° C to + 55 ° C

Temperature control

Comfort controller, factory setting + 35 ° C

Power consumption L35L35 60 Hz / W

347 W

Type of connection

Pluggable terminal strip

Texts for tenders:

Roof-mounted cooling unit Rittal TopTherm PLUS
with RiNano coating and integral condensate evaporation
Useful cooling output to DIN 3168 L35 L35 500/586 W

Data sheet

SK 3382.500



Rated operating voltage 230 V, 1~, 50/60 Hz
Power consumption Pel to DIN 3168 L35 L35 302/347 W
Dimensions W x H x D [mm] 597 x 415 x 375
Refrigerant R 134 a
Temperature range 20°C to 55°C
Temperature control and monitoring via
comfort controller with two floating fault
signal contacts and connection for door-operated
switch and condensate warning.
Factory setting 35°C
Connection via pluggable terminal strip
Protection category to EN 60 529/10.91
External circuit IP 34 / internal circuit IP 54
Weight 30 kg
Colour RAL 7035