

Data sheet

SK 3383.100



Main data:

Model No.:	SK 3383.100
Designation:	TopTherm PLUS roof-mounted cooling unit, 1000 W, basic control., 230 V, 50/60 Hz, RiNano coating / condensate evaporation
Variant:	Basiscontroller
Packs of:	1 ST
W x H x D:	595 mm x 415 mm x 475 mm
Mounting surface:	n/a
Volume:	202,61 dm ³
Net weight:	40,00 kg
EAN:	4028177323186
Customs number:	84158200
Protection categories:	n/a

You can find the product in [Catalogue 32, page 637](#)

Approbationen:

CE	3 237 305
CSA	1695558
CUR	SA 8250
GS	44 315 09 368698
UL	Bestätigung Type 12
UR	SA 8250

Article features:

Power consumption L35L50 60 Hz / W
950
Temperature range °C
+ 20 ° C - + 55 ° C (Setting range +30°C to +55°C)

Data sheet

SK 3383.100



Rated operating voltage V/Hz
230 V, 50/60 Hz
Useful cooling output L35L35 50 Hz / W
1000
Useful cooling out L35L35 60 Hz / W
1080
Useful cooling output L35L50 50 Hz / W
760
Useful cooling output L35L50 60 Hz / W
820
Rated current 50 Hz / A
5.2
Rated current 60 Hz / A
5.4
Start-up current 50 Hz / A
16
Start-up current 60 Hz / A
16
Pre-fuse T 50 Hz / A
10.0
Pre-fuse T 60 Hz / A
10.0
Power consumption L35L35 50 Hz / W
750
Power consumption L35L35 60 Hz / W
850
Protection category internal circuit
IP 54

Data sheet

SK 3383.100



Product notes

Special voltages available on request.

We reserve the right to make technical modifications.

Temperature control

Basic controller, factory setting + 35 ° C

Air throughput, internal circuit / m3/h

440

Air throughput, external circuit / m3/h

1760

Colour

RAL 7035

Weight / kg

40 Kg

Duty cycle

100 %

Protection category external circuit

IP 34

Operating pressure p. max

25 bar

Refrigerant

R134a

Supply includes

Fully wired, ready for connection, including drilling
template, eyebolt,

assembly parts and multilingual assembly instructions

Type of connection

Pluggable terminal strip

Power consumption L35L50 50 Hz / W

860

Data sheet
SK 3383.100

