

Data sheet

SK 3383.500



Main data:

Model No.:	SK 3383.500
Designation:	TopTherm PLUS roof-mounted cooling unit, 1000 W, comfort control. 230 V, 50/60 Hz, RiNano coating / condensate evaporation
Variant:	Comfortcontroller
Packs of:	1 ST
W x H x D:	595 mm x 415 mm x 475 mm
Mounting surface:	n/a
Volume:	192,19 dm ³
Net weight:	43,70 kg
EAN:	4028177323216
Customs number:	84158200
Protection categories:	n/a

Approbationen:

CE	3 237 305
CSA	1695558
CUR	SA 8250
GS	44 315 09 368698
UL	Bestätigung Type 12
UR	SA 8250

Article features:

Operating pressure p. max
25 bar
Start-up current 50 Hz / A
16

Data sheet

SK 3383.500



Rated operating voltage V/Hz
230, 50/60
Rated current 50 Hz / A
5.2
Power consumption L35L50 50 Hz / W
860
Useful cooling output L35L35 60 Hz / W
1080
Duty cycle
100 %
Rated current 60 Hz / A
5.4
Start-up current 60 Hz / A
16
Refrigerant
R134a
Useful cooling output L35L50 50 Hz / W
760
Temperature range °C
+ 20 ° C to + 55 ° C
Protection category external circuit
IP 34
Protection category internal circuit
IP 54
Useful cooling output L35L35 50 Hz / W
1000
Colour
RAL 7035

Data sheet

SK 3383.500



Air throughput external circuit / m³/h

1760

Air throughput, internal circuit / m³/h

440

Product notes

Special voltages available on request.

We reserve the right to make technical modifications.

Power consumption L35L50 60 Hz / W

950

Temperature control

Comfort controller, factory setting + 35 °C

Pre-fuse T 60 Hz / A

10.0

Power consumption L35L35 50 Hz / W

750

Power consumption L35L35 60 Hz / W

850

Useful cooling output L35L50 60 Hz / W

820

Weight / kg

40 kg

Type of connection

Pluggable terminal strip

Supply includes

Fully wired ready for connection, including drilling
template, eyebolt,

assembly parts and multilingual assembly instruction.

Pre-fuse T 50 Hz / A

10.0

Data sheet
SK 3383.500

