

# Data sheet

## SK 3383.540



### Main data:

<b>Model No.:</b>	SK 3383.540
<b>Designation:</b>	TopTherm PLUS roof-mounted cooling unit, 1000 W, comfort control. 400 V, 50/60 Hz, RiNano coating / condensate evaporation
<b>Variant:</b>	Comfortcontroller
<b>Packs of:</b>	1 ST
<b>W x H x D:</b>	595 mm x 415 mm x 475 mm
<b>Mounting surface:</b>	n/a
<b>Volume:</b>	192,19 dm <sup>3</sup>
<b>Net weight:</b>	46,00 kg
<b>EAN:</b>	4028177323223
<b>Customs number:</b>	84158200
<b>Protection categories:</b>	n/a

### Approbationen:

<b>CE</b>	3 237 305
<b>CSA</b>	1695558
<b>CUR</b>	SA 8250
<b>GS</b>	44 315 09 368698
<b>UL</b>	Bestätigung Type 12
<b>UR</b>	SA 8250

### Article features:

Rated current 50 Hz / A  
2.9  
Useful cooling output L35L50 50 Hz / W  
760

# Data sheet

## SK 3383.540



Power consumption L35L50 50 Hz / W  
870

Power consumption L35L35 60 Hz / W  
860

Power consumption L35L35 50 Hz / W  
780

Pre-fuse T 60 Hz / A  
6.3 - 10.0

Pre-fuse T 50 Hz / A  
6.3 - 10.0

Start-up current 60 Hz / A  
9.3

Start-up current 50 Hz / A  
8.5

Rated current 60 Hz / A  
2.9

Rated operating voltage V/Hz  
400 (\*), 2~, 50/60

Useful cooling output L35L50 60 Hz / W  
820

Power consumption L35L50 60 Hz / W  
955

Temperature control  
Comfort controller, factory setting + 35 ° C

Useful cooling output L35L35 50 Hz / W  
1000

Operating pressure p. max  
25 bar

# Data sheet

## SK 3383.540



Air throughput external circuit / m<sup>3</sup>/h

1760

Refrigerant

R134a

Product notes

Special voltages available on request.

We reserve the right to make technical modifications.

Air throughput, internal circuit / m<sup>3</sup>/h

440

Supply includes

Fully wired ready for connection, including drilling  
template, eyebolt,

assembly parts and multilingual assembly instructions.

Colour

RAL 7035

Weight / kg

46 kg

Type of connection

Pluggable terminal strip

Duty cycle

100 %

Protection category internal circuit

IP 54

Protection category external circuit

IP 34

Temperature range °C

+ 20 ° C to + 55 ° C

Useful cooling output L35L35 60 Hz / W

1080

Data sheet  
**SK 3383.540**

