

Data sheet

SK 3385.540



Main data:

Model No.:	SK 3385.540
Designation:	Top Therm Blue e roof-m. cooling unit, 2000 W, comfort contr., 400 V, 50/60 Hz, RiNano coating / condensate evaporation
Variant:	Comfortcontroller, Comfortcontroller, Comfortcontroller, Comfortcontroller, Comfor
Packs of:	1 ST
W x H x D:	595 mm x 415 mm x 475 mm
Mounting surface:	n/a
Volume:	203,38 dm ³
Net weight:	53,20 kg
EAN:	4028177323285
Customs number:	84158200
Protection categories:	n/a

Approbationen:

CE	3 237 305
CSA	1695566
CUR	SA 8250
GS	44 315 09 368698
UL	Bestätigung Type 12
UR	SA 8250

Article features:

Temperaturbereich °C	+ 20 ° C to + 55 ° c Useful cooling output L35L35 60 Hz / W 2140
-----------------------------	--

Data sheet

SK 3385.540



Power consumption L35L50 60 Hz / W
1310

Rated operating voltage V/Hz

400 (*), 2 ~, 50/60

(*) internal transformer - settings according to rated current if

transformer circuit-breakers are used.

Useful cooling output L35L35 50 Hz / W
2000

Power consumption L35L35 50 Hz / W
1020

Useful cooling output L35L50 50 Hz / W
1409

Rated current 50 Hz / A
3.8

Rated current 60 Hz / A
4.3

Start-up current 50 Hz / A
10.0

Start-up current 60 Hz / A
12.0

Pre-fuse T 60 Hz / A
6.3 - 10.0

Power consumption L35L50 50 Hz / W
1441

Supply includes

Fully wired ready for connection, including drilling template, eyebolt,

assembly parts and multilingual assembly instructions.

Power consumption L35L35 60 Hz / W

Data sheet

SK 3385.540



1235

Protection category external circuit

IP 34

Useful cooling output L35L50 60 Hz / W

1511

Type of connection

Pluggable terminal strip

Air throughput external circuit / m³/h

1820

Temperature control

Comfort controller (factory setting + 35 ° C)

Weight / kg

48 kg

Operating pressure p. max

25 bar

Duty cycle

100 %

Colour

RAL 7035

Air throughput, internal circuit / m³/h

470

Product notes

Special voltages available on request. We reserve the right to make technical modifications.

Refrigerant

R134a

Pre-fuse T 50 Hz / A

6.3 - 10.0

Data sheet

SK 3385.540



Protection category internal circuit
IP 54

Texts for tenders:

Roof-mounted cooling unit Rittal TopTherm Blue e
with RiNano coating and integral condensate evaporation
Useful cooling output to DIN 3168 L35 L35 2000/2140 W
Rated operating voltage 400 V, 2~, 50/60 Hz
Power consumption Pel to DIN 3168 L35 L35 1020/1235 W
Dimensions W x H x D [mm] 597 x 415 x 475
Refrigerant R 134 a
Temperature range 20°C to 55°C
Temperature control and monitoring via
comfort controller with two floating fault
signal contacts, connection for door-operated switch
and condensate warning.
Factory setting 35°C
Connection via pluggable terminal strip
Protection category to EN 60 529/10.91
External circuit IP 34 / internal circuit IP 54
Weight 48 kg
Colour RAL 7035