

Data sheet

SK 3387.540



Main data:

Model No.:	SK 3387.540
Designation:	TopTherm Blue e roof-mount. cooling unit, 4000 W, comfort contr., 400/460 V, 50/60 Hz, RiNano coat. / cond. evaporat.
Variant:	Comfortcontroller, Comfortcontroller, Comfortcontroller, Comfortcontroller, Comfor
Packs of:	1 ST
W x H x D:	795 mm x 470 mm x 580 mm
Mounting surface:	n/a
Volume:	348,16 dm ³
Net weight:	73,15 kg
EAN:	4028177323322
Customs number:	84158200
Protection categories:	n/a

Approbationen:

CE	3 237 305
CSA	1695574
CUR	SA 8250
GS	44 315 09 368698
UL	Bestätigung Type 12
UR	SA 8250

Article features:

Temperature range °C
+ 20 ° C to + 55 ° C
Air throughput external circuit / m3/h
3870

Data sheet

SK 3387.540



Power consumption L35L50 50 Hz / W
1880

Power consumption L35L35 60 Hz / W
2070

Duty cycle
100 %

Start-up current 50 Hz / A
17.0

Rated current 60 Hz / A
4.2

Refrigerant
R134a

Product notes

Special voltages available on request.

We reserve the right to make technical modifications.

Temperature control

Comfort controller (factory setting + 35 ° C)

Weight / kg
77 kg

Type of connection

Pluggable terminal strip

Protection category internal circuit
IP 54

Rated operating voltage V/Hz
400, 50/460, 60, ~3

Useful cooling output L35L35 60 Hz / W
4200

Colour

Data sheet

SK 3387.540



RAL 7035
Pre-fuse T / A
Motor circuit breaker 10 A/10 A
Power consumption L35L35 60 Hz / W
2340
Air throughput, internal circuit / m³/h
1420
Useful cooling output L35L50 50 Hz / W
3250
Useful cooling output L35L50 60 Hz / W
3490
Rated current 50 Hz / A
4.2
Start-up current 60 Hz / A
19.0
Useful cooling output L35L35 50 Hz / W
4000
Protection category external circuit
IP 34
Power consumption L35L50 60 Hz / W
2350
Power consumption L35L35 50 Hz / W
1630

Texts for tenders:

Roof-mounted cooling unit Rittal TopTherm Blue e
with RiNano coating and integral condensate evaporation
Useful cooling output to DIN 3168 L35 L35 4000/4200 W
Rated operating current 400 V, 50 Hz - 460 V,

Data sheet

SK 3387.540



3~, 60 Hz

Power consumption Pel to DIN 3168 L35 L35 1630/2070 W

Dimensions W x H x D [mm] 796 x 470 x 580

Refrigerant R 134 a

Temperature range 20°C to 55°C

Temperature control and monitoring via comfort controller with two floating fault signal contact, connection for door-operated switch and condensate warning.

Factory setting 35°C

Connection via pluggable terminal strip

Protection category to EN 60 529/10.91

External circuit IP 34 / internal circuit IP 54

Weight 77 kg

Colour RAL 7035