

Rittal – The System.

Faster – better – everywhere.

NH fuse-switch- disconnectors, size 000 – SV 3431.030

Date : Jul 10, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH fuse-switch-disconnectors, size 000 – SV 3431.030

created: 10.07.2018 on www.rittal.com/com-en



Product description

Material: Fibreglass-reinforced polyamide
Fire protection corresponding to UL 94-V0
Contact tracks: Silver-plated hard copper

Colour: Chassis: RAL 7035
Cover: RAL 7001

Basis of test: IEC/DIN EN 60 947-3
DIN EN 60 269-2 (fuse inserts)

Product features

Design: Size: 000

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 53 mm
Height: 213 mm

Type of electrical connection: Box terminal

Rated operating voltage: 690 V, 3~

| | |
|---|---|
| Connection for round conductor cross-sections: | 2,5 mm ² - 50 mm ² |
| Rated operating current max.: | 100 A |
| Cable outlet: | Bottom |
| Packs of: | 1 pc(s). |
| Weight/pack: | 0.6 kg |
| EAN: | 4028177628731 |
| Customs tariff number: | 85369095 |
| ETIM 6.0: | EC001040 |
| ETIM 5.0: | EC001040 |
| eCl@ss 6.0/6.1: | 27371401 |
| eCl@ss 5.1/5.1.4: | 27370302 |
| Product description (long): | SV NH fuse-switch disconnecter, size 000, 100 A, 690 V, 3-pole, box terminal, cable outlet bottom |
| Approvals | |
| Certificates: | EAC |
| Declarations: | Declaration of conformity |