## Rittal - The System.


Faster – better – everywhere.

## Conductor connection clamp – SV 3453.500



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Conductor connection clamp — SV 3453.500 created: 12.01.2022 build on www.rittal.com/uk-en



Product description	
Description:	For connecting round conductors and laminated copper bars.
Material:	Sheet steel
Surface finish:	Zinc-plated, passivated
Note:	Wire end ferrules should be used with fine wire conductors
Product description	
To fit busbars:	Cross-section (thickness): 5 mm
Clamping area for laminated copper bars:	Width: 16.5 mm Height: 15 mm
Connection for round conductor cross-sections:	35 mm² - 70 mm²
Packs of:	15 pc(s).
Weight/pack:	1.68 kg
Copper weight (kg per piece):	0
EAN:	4028177042704
Customs tariff number:	85369010

© Rittal 2022

ETIM 7.0:	EC000001
ETIM 6.0:	EC000001
eCl@ss 8.0/8.1:	27141146
eCl@ss 6.0/6.1:	27141146
Product description:	SV Conductor connection clamp, 35-70 mm², clamping area WH: 16,5x15 mm, for bar thickness 5 mm
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2022