Rittal – The System.

Faster – better – everywhere.

Conductor connection clamp - SV 3459.500




ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Conductor connection clamp – SV 3459.500 created: 26.01.2022 build on www.rittal.com/uk-en



| Product description | |
|---|--|
| Description: | For connecting round conductors and laminated copper bars. |
| Material: | Sheet steel |
| Surface finish: | Zinc-plated, passivated |
| Note: | Wire end ferrules should be used with fine wire conductors |
| Product description | |
| To fit busbars: | Cross-section (thickness): 10 mm |
| Clamping area for laminated copper bars: | Width: 22.5 mm Height: 20 mm |
| Connection for round conductor cross- sections: | 70 mm² - 185 mm² |
| Packs of: | 15 pc(s). |
| Weight/pack: | 2.04 kg |
| Copper weight (kg per piece): | 0 |
| EAN: | 4028177042780 |
| Customs tariff number: | 85369010 |

| ETIM 7.0: | EC000001 |
|----------------------|--|
| ETIM 6.0: | EC000001 |
| eCl@ss 8.0/8.1: | 27141146 |
| eCl@ss 6.0/6.1: | 27141146 |
| Product description: | SV Conductor connection clamp, 70-185 mm², clamping area WH: 22,5x20 mm, for bar thickness 10 mm |
| Approvals | |
| Approvals: | C-UR UR |
| Certificates: | EAC |
| Declarations: | Declaration of conformity |
| | |