Rittal - The System.

Faster - better - worldwide.

Standard light – SZ 4138.150

Date: Nov 11, 2013



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Standard light — SZ 4138.150 created: 11.11.2013 on www.rittal.com/com-en



Product desc	cription
--------------	----------

Packs of: 1 pc(s).

EAN: 4028177320710

Customs tariff number:

94054095

Product features

Dimensions: Width: 452 mm

> Height: 117 mm Depth: 50 mm

Rated operating

voltage:

230 V AC/1~/50 Hz

Power consumption: 14 W

Equipment Ballast: Magnetic ballast

(electrical): Light: Fluorescent lamp, base G13

Protection category: I (protectively earthed)

Connection options: Door-operated switch Power supply via connectors

Through-wiring (creating rows of lights)

Jack/socket (type): D, earthing-pin (type F, CEE 7/4)

Integral door-operated switch: x

Switch (type): Integral, on/off/door-operated switch mode

Light - installation

type:

Screw-fastening

Light - mounting

option:

TS vertical section, with adaptor bracket AE/CM/TP, with universal bracket

© Rittal 2013 1

Approvals	
Certificates	Sorry, there is currently no information available
Declarations	型 Declaration of conformity (EN, DE)
Approvals	Sorry, there is currently no information available
Downloads / CAD	
Documentation	Sorry, there is currently no information available
Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available
Data sheets	Sorry, there is currently no information available
CAD-Drawing	Sorry, there is currently no information available

© Rittal 2013 2

Rittal – The System.

Faster - better - worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG Postbox 1662 · D-35726 Herborn

Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319

E-Mail: info@rittal.com · www.rittal.com

