Rittal - The System.

Faster - better - worldwide.

Standard light – SZ 4138.180

Date: Nov 10, 2013



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Standard light — SZ 4138.180 created: 10.11.2013 on www.rittal.com/com-en



Product descri	ption
----------------	-------

Packs of: 1 pc(s).

EAN: 4028177092273

Customs tariff number:

94054095

Product features

Dimensions: Width: 682 mm

> Height: 117 mm Depth: 50 mm

Rated operating

voltage:

230 V AC/1~/50 Hz

Power consumption: 18 Btu/h

Equipment Ballast: Magnetic ballast

(electrical): Light: Fluorescent lamp, base G13

Protection category: I (protectively earthed)

Connection options: Door-operated switch Power supply via connectors

Through-wiring (creating rows of lights)

Jack/socket (type): D, earthing-pin (type F, CEE 7/4) Switch (type): Integral, on/off/door-operated switch mode

Light - installation

type:

Screw-fastening

Light - mounting

option:

TS vertical section, with adaptor bracket AE/CM/TP, with universal bracket AE, with rail for interior installation

© Rittal 2013

1

Approvals	
Certificates	Sarry there is currently no information available
Ceruncates	Sorry, there is currently no information available
Declarations	☑ Declaration of conformity (EN, DE)
Approvals	Sorry, there is currently no information available
Downloads / CAD	
Documentation	¹ Instructions (SV, DE, ES, EN, FR, NL, IT)
Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available
Data sheets	Sorry, there is currently no information available
CAD-Drawing	Sorry, there is currently no information available

© Rittal 2013 2

Rittal – The System.

Faster - better - worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG Postbox 1662 · D-35726 Herborn

Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319

E-Mail: info@rittal.com · www.rittal.com

