Rittal - The System.

Faster - better - worldwide.

Courtesy light − SZ 4139.140

Date: Nov 10, 2013



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Courtesy light – SZ 4139.140 created: 10.11.2013 on www.rittal.com/com-en



Product de	escription
------------	------------

Packs of: 1 pc(s).

EAN: 4028177092327

Customs tariff number:

94054095

Product features

Dimensions: Width: 452 mm

> Height: 117 mm Depth: 50 mm

Rated operating

voltage:

100 - 240 V AC/1~/50 Hz 100 - 240 V AC/1~/60 Hz

14 W Power consumption:

Equipment Ballast: Wide-range electronic ballast (electrical): Light: Fluorescent lamp, base G13

Protection category: I (protectively earthed)

Connection options:

Power supply via connectors

Door-operated switch

Through-wiring (creating rows of lights)

Jack/socket (type): D, earthing-pin (type F, CEE 7/4) Switch (type): Integral, on/off/door-operated switch mode

Light - installation

type:

Screw-fastening

Light - mounting option:

TS roof frame (horizontal section), direct TS vertical section, with adaptor bracket

© Rittal 2013 1

Light cover:	x
Approvals	
Certificates	Sorry, there is currently no information available
Declarations	型 Declaration of conformity (EN, DE)
Approvals	Sorry, there is currently no information available
Downloads / CAD	
Documentation	¹ Instructions (SV, DE, ES, EN, FR, NL, IT)
Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available
Data sheets	Sorry, there is currently no information available
CAD-Drawing	Sorry, there is currently no information available

© Rittal 2013 2

Rittal – The System.

Faster - better - worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG Postbox 1662 · D-35726 Herborn

Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319

E-Mail: info@rittal.com · www.rittal.com

