Rittal – The System.

Faster – better – worldwide.



RITTAL

ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Courtesy light – SZ 4139.190 created : 11.11.2013 on www.rittal.com/com-en



Product description	
Packs of:	1 pc(s).
EAN:	4028177320758
Customs tariff number:	94054095
Product features	
Dimensions:	Width: 682mm Height: 117mm Depth: 50mm
Rated operating voltage:	100 – 240 V AC/1~/50 Hz 100 – 240 V AC/1~/60 Hz
Power consumption:	18 W
Equipment (electrical):	Ballast: Wide-range electronic ballast Light: Fluorescent lamp, base G13 Protection category: I (protectively earthed) Connection options : Power supply via connectors Door-operated switch Through-wiring (creating rows of lights) Jack/socket (type): D, earthing-pin (type F, CEE 7/4) Integral door-operated switch: x Switch (type): Integral, on/off/door-operated switch mode
Light – installation type:	Screw-fastening
Light – mounting	TS roof frame (horizontal section), direct

option:	TS vertical section, with adaptor bracket AE/CM/TP, with universal bracket AE, with rail for interior installation
Light cover:	x
Approvals	
Certificates	Sorry, there is currently no information available
Declarations	Declaration of conformity (EN, DE)
Approvals	Sorry, there is currently no information available
Downloads / CAD	
Documentation	Instructions (SV, DE, ES, EN, FR, NL, IT)
Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available
Data sheets	Sorry, there is currently no information available
CAD-Drawing	Sorry, there is currently no information available

Rittal – The System.

Faster – better – worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

