

Rittal – The System.

Faster – better – everywhere.

Courtesy light – SZ **4139.300**

Date : Jul 1, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Courtesy light – SZ 4139.300

created : 01.07.2014 on www.rittal.com/com-en



Product description

Supply includes:

- Courtesy light
- Light
- Light cover
- Assembly parts

Packs of:

- 1 pc(s).

EAN:

- 4028177092365

Customs tariff number:

- 94054095

Product features

Design:

- without door operated switch

Dimensions:

- Width: 987 mm
- Height: 117 mm
- Depth: 50 mm

Rated operating voltage:

- 100 V - 240 V, 1~, 50 Hz/60 Hz

Power consumption:

- 30 W

Equipment (electrical):

- Ballast: Wide-range electronic ballast

- Light: Fluorescent lamp, base G13
- Protection category: I (protectively earthed)
- Connection options: Power supply via connectors
- Door-operated switch
- Through-wiring (creating rows of lights)
- Jack/socket (type): D, earthing-pin (type F, CEE 7/4)

Light – installation type:

- Screw-fastening

Light – mounting option:

- TS roof frame (horizontal section), direct
- TS vertical section, with adaptor bracket
- AE/CM/TP, with universal bracket
- AE, with rail for interior installation

Light cover:


- yes

Weight:

- 2.96 kg


Approvals

Declarations:

-  [Declaration of conformity \(DE\)](#)

Downloads

Documentation:

-  [Instructions \(SE, DE, ES, EN, FR, NL, IT\)](#)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP