

# Rittal – The System.

Faster – better – worldwide.

## Compact light – SZ 4140.010

Date : Nov 11, 2013

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Compact light – SZ 4140.010

created : 11.11.2013 on www.rittal.com/com-en



## Product description

**Description:** Slimmer: Around 50% less height and depth and also around 75% less volume than conventional lights. Faster: Universal fast attachment via clips, screws, or powerful magnets (optional). Simply slide in at the side or rear, fit the light, and it's done! Brighter: Up to 75% greater luminous efficiency from the lamp with the same power helps to cut electricity costs. Door-operated switch can also be connected via a 2-pole connection.

**Colour:** Similar to RAL 7035

**Protection category  
IP to IEC 60 529:** IP 20

**Supply includes:** Compact light with clip and screw mounting kits  
Assembly parts

**Packs of:** 1 pc(s).

**EAN:** 4028177522725




**Customs tariff  
number:** 94054095

## Product features

**Dimensions:** Height: 59 mm  
Depth: 24 mm

**Rated operating  
voltage:** 100 – 240 V AC/1~/50 Hz  
100 – 240 V AC/1~/60 Hz  
Voltage tolerance:  $\pm 10\%$

**Mounting dimensions:** Mounting distance – clip/magnet: 400 mm  
Mounting distance – screw attachment: 475 mm

<b>Rated current:</b>	At 230 V/50 Hz: 0.04 A/0.09 A At 110 V/60 Hz: 0.08 A/0.15 A
<b>Power consumption:</b>	8 W
<b>Equipment (electrical):</b>	Ballast: Wide-range electronic ballast Light: Fluorescent lamp T5 Protection category: II (all-insulated) Connection options : Integral connection cable with open end Door-operated switch Length of connection cable: 3 m Colour of cable: Yellow Switch (type): Integral, on/off/door-operated switch mode
<b>Light – installation type:</b>	Clip attachment Magnetic attachment (accessory) Screw-fastening
<b>Light – mounting option:</b>	TS roof frame (horizontal section), direct TS vertical section, direct AE/CM/TP, with magnetic attachment
<b>Cable deflector across rear possible:</b>	x
<b>Light cover:</b>	x
<b>Approvals</b>	
<b>Certificates</b>	Sorry, there is currently no information available
<b>Declarations</b>	 Declaration of conformity (DE, EN)
<b>Approvals</b>	Sorry, there is currently no information available
<b>Downloads / CAD</b>	
<b>Documentation</b>	 Instructions (RU)  Instructions (SV, FR, NL, EN, JP, ES, DE, IT)
<b>Characteristic curves</b>	Sorry, there is currently no information available
<b>Videos</b>	Sorry, there is currently no information available
<b>Data sheets</b>	Sorry, there is currently no information available
<b>CAD-Drawing</b>	Sorry, there is currently no information available

# Rittal – The System.

---

**Faster – better – worldwide.**

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG  
Postbox 1662 · D-35726 Herborn  
Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319  
E-Mail: [info@rittal.com](mailto:info@rittal.com) · [www.rittal.com](http://www.rittal.com)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

