

Rittal – The System.

Faster – better – worldwide.

LED system light – SZ 4140.820

Date : Jan 13, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



LED system light 24 V DC version – SZ 4140.820

created : 13.01.2014 on www.rittal.com/com-en




Product description

Benefits:	Max. EMC capacity. Safe, thanks to operation in the extra-low safety voltage range. Economical energy use. Low-maintenance thanks to the use of LEDs. May be connected to a door-operated switch.
Function principle:	Integral through-wiring. Universal attachment options. Vertically hinged light cone
Material:	Light body: Extruded aluminium Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS
Colour:	Similar to RAL 7035
Protection category IP to IEC 60 529:	IP 20
Supply includes:	LED system light with clip and screw mounting kits Assembly parts
Note:	Only intended for use in enclosures and sealed cases! When using on customer-supplied power packs, it is important to obtain the requisite approvals depending on the application!
Packs of:	1 pc(s).
EAN:	4028177630130
Customs tariff number:	94054099


Product features

Dimensions:	Width: 330 mm Height: 32.8 mm Depth: 20.64 mm
Rated operating voltage:	24 V DC/-/ Voltage tolerance: $\pm 10 \%$
Mounting dimensions:	Mounting distance – clip/magnet: 275 mm Mounting distance – screw attachment: 350 mm
Rated current:	With DC (max.): 0.08 A Note Maximum baying up to a total rated current strength of 2 amps.
Equipment (electrical):	Light: LEDs, cold white Protection category: III (SELV) Connection options : Power supply via connectors Door-operated switch Through-wiring (creating rows of lights) Switch (type): Integral, on/off/door-operated switch mode
Number of LEDs:	20
Light – installation type:	Clip attachment Magnetic attachment (accessory) Screw-fastening
Light – mounting option:	TS roof frame (horizontal section), direct TS roof frame (horizontal section), direct AE/CM/TP, with magnetic attachment
Light cover:	x
Light cone adjustment:	x

Approvals

Certificates	Sorry, there is currently no information available
Declarations	 Declaration of conformity (DE, EN)
Approvals	Sorry, there is currently no information available

Downloads / CAD

Documentation	 Instructions (SV, FR, NL, EN, JP, ES, DE, IT)
Characteristic curves	Sorry, there is currently no information available

Videos Sorry, there is currently no information available

Data sheets Sorry, there is currently no information available

CAD-Drawing Sorry, there is currently no information available

Treiber/Software Sorry, there is currently no information available

Rittal – The System.

Faster – better – worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postbox 1662 · D-35726 Herborn
Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

