

Rittal – The System.

Faster – better – everywhere.

► Universal light with integral motion detector – SZ 4155.510

Date : Dec 13, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Universal light with integral motion detector – SZ 4155.510

created: 13.12.2017 on www.rittal.com/com-en



Product description

Description: Compact fluorescent tube 18 W with high luminosity.

Benefits: Simple, fast assembly

Material: Plastic

Supply includes: Universal light
Integral motion detector
Light
Light cover
Assembly parts

Product features

Dimensions: Width: 345 mm
Height: 95 mm
Depth: 55 mm

Rated operating voltage: 110 V - 240 V, 1~, 50 Hz/60 Hz

Installation options: TS horizontal section of the roof frame: direct
TS, SE vertical section: with TS adaptor bracket
SE sections at the front and rear of the roof frame: with TS adaptor bracket
SE extrusions at the side of the roof frame: direct
AE, CM, TP: with universal bracket
AE: with rail for interior installation

Operating temperature: Operation (environment): -15°C...+45°C
Bearing: -20°C...+70°C

Power consumption:	18 W
Equipment (electrical):	Ballast: Wide-range electronic ballast Light: Compact fluorescent lamp, base 2G11 Integral motion detector: yes Switch (type): Integral, on/off/motion detector mode
Rated insulation voltage:	250 V AC
Rated impulse withstand voltage, phase to phase:	2500 V AC
Protection category:	I (PE conductor)
Connection options:	Power supply via connectors Through-wiring (creating rows of lights)
Light – installation type:	Screw-fastening
Light cover:	yes
Packs of:	1 pc(s).
Weight/pack:	0.88 kg
EAN:	4028177679849
Customs tariff number:	94054095
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Product description (long):	SZ Universal light, WHD: 343x95x55 mm, 18 W, 110-240 V, 50/60 Hz, with integral motion detector, UL

Approvals

Approvals: CSA
UL
VDE

Certificates: EAC

Declarations: Declaration of conformity
