Rittal – The System.

Faster – better – everywhere.



......

6.6

6

1

0

0.00

C

e

0

C

C

0

0

0

0

A

TS 4599.100 Support strip

State: 13/01/2022 (Source: rittal.com/com-en)



POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

TS 4599.100 - Support strip for VX, TS, SE, CM, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.



Features

Product description	For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.
Material	Sheet steel
Surface finish	Zinc-plated
Supply includes	Assembly parts
Length	320 mm
Suitable for door width	380 mm
Installation options	In the AX enclosure door with cam lock On the perforated door strip in AX stainless steel
Assembly instruction	For installation in AX stainless steel, only in conjunction with perforated door strip
Technical specifications	4.5 mm diameter hole on a 25 mm DIN pitch pattern.
To fit	Enclosure type: AX with cam AX stainless steel Suitable for width or depth: 380 mm
Weight/pack	3.3 kg
Packs of	20 Stück
ETIM 7.0	EC002620

Features

ECLASS 8.0

27189261